

DESCRIPTION

CRYSTALLINE ANTHRACYCLINE ANTIBIOTIC AND PROCESS FOR PRODUCING THE SAME

5

Technical Field


This invention relates to novel crystalline forms of an anthracycline antibiotic, particularly daunomycin (also known as daunorubicin), and a process for producing the same.

10

Background Art

Daunomycin (also known as daunorubicin; hereinafter abbreviated as DM), which is an anthracycline antibiotic represented by the following formula (I)

15



20

is known to be obtained from a culture medium of an actinomycete, and has a wide anticancer spectrum against experimental animal tumors. As a matter of fact, DM is being widely used as a chemotherapeutic agent for cancer in clinical applications.

However, the currently available bulk form of DM (DM hydrochloride) is an amorphous powder or a solid which is tentatively classified as crystalline but has high hygroscopicity and poor stability. From the viewpoint of the preparation of DM into medicines, the

30

physical and chemical properties of not only its final bulk powder but also its intermediate products have a great significance. For example, poor chemical stability requires great caution in storage, and high hygroscopicity makes its handling difficult. Moreover, with
5 consideration for its use as a drug, any residual solvent may constitute a fatal shortcoming.

Accordingly, an object of the present invention is to provide a solid product of DM hydrochloride having excellent chemical stability and, preferably, further having low hygroscopicity and an
10 allowable residual solvent content.

Disclosure of the Invention

The present inventors made repeated investigations with a view to solving the above-described problems and have now found
15 that the crystallization of DM hydrochloride by using a certain solvent system yields a specific crystalline form of DM hydrochloride having excellent chemical stability and, in some instances, this crystalline form also has low hygroscopicity and can solve the problem with residual solvent.

Thus, according to the present invention, there is provided
20 a crystalline form of DM hydrochloride having at least characteristic 2 θ values (in degrees) of 6.18, 7.88, 9.82, 11.60, 13.30, 15.80, 20.88 and 23.12 as measured by the X-ray powder diffraction method.

According to the present invention, there is also provided
25 a process for producing the aforesaid crystalline form of DM hydrochloride from a solution containing DM hydrochloride, the process comprising the steps of preparing the aforesaid solution by using a solvent system composed of a poor solvent for the antibiotic and a good solvent which is miscible with the poor solvent and capable of
30 dissolving the antibiotic; and subjecting the solution so prepared to a crystallization treatment.

Brief Description of the Drawing

FIG. 1 is a chart showing the results of X-ray powder diffraction analysis of DM hydrochloride powders and various crystalline forms of DM hydrochloride. In this chart, b) shows the result of X-ray powder diffraction analysis of a crystalline form of DM hydrochloride in accordance with the present invention; a), d), e) and f) show the results of X-ray powder diffraction analysis of amorphous DM hydrochloride powders (comparative powders); and c), g) and h) show the results of X-ray powder diffraction analysis of solid forms of DM hydrochloride which are regarded as crystalline but do not show the properties of the crystalline form in accordance with the present invention (comparative crystalline forms).

Specific Description of the Invention

Specifically, the crystalline form of DM hydrochloride in accordance with the present invention are characterized by having at least characteristic 2 θ values (in degrees) of 6.18, 7.88, 9.82, 11.60, 13.30, 15.80, 20.88 and 23.12 as measured by the X-ray powder diffraction method (the Debye-Scherrer method) [see b) in FIG. 1]. The term "crystalline form" as used herein means a single crystal or a mass of such crystals, and the aforesaid results of X-ray powder diffraction analysis are those obtained from such masses.

The crystalline form in accordance with the present invention are clearly distinguished from amorphous powders [corresponding to those shown as a), d), e) and f) in FIG. 1] and solid forms tentatively regarded as crystalline [corresponding to those shown as c), g) and h) in FIG. 1]. Moreover, as will be described later, the crystalline form b) have very excellent properties from the viewpoints of hygroscopicity, residual solvent and chemical stability.

Generally and not by way of limitation, the process for producing the aforesaid crystalline form in accordance with the

present invention comprises the steps of preparing a solution by dissolving a DM hydrochloride powder having a relative purity of greater than 90% in a solvent capable of dissolving the DM; and crystallizing the DM by adding to the solution a solvent which is
5 miscible with the aforesaid solvent but is a poor solvent for DM.

It is important to use a solvent containing at least 1-butanol as the aforesaid poor solvent. Typical examples of such solvents include 1-butanol alone and solvent mixtures composed of 1-butanol and other organic solvents (e.g., acetone, hexane and diisopropyl
10 ether). On the other hand, as the solvent capable of dissolving DM, there may be used any solvent that can dissolve DM, is miscible the aforesaid poor solvent, and hence suits the purpose of the present invention. Typical examples of such solvents include, but are not limited to, water, methanol, ethanol, and mixtures of two or more of
15 them.

In accordance with a preferred embodiment, the production process of the present invention comprises the steps of preparing a solution by dissolving a DM hydrochloride powder having a relative purity of greater than 90% in methanol (for example, by using the
20 DM hydrochloride powder and methanol in a weight ratio of 1 : 5 to 1 : 20); and crystallizing the DM by adding 1-butanol or a mixture of 1-butanol and acetone, hexane or diisopropyl ether (for example, containing up to 60% of acetone, hexane or diisopropyl ether) to the aforesaid solution in an amount of about 1 to 20 parts by volume as
25 based on the methanol.

When the expression "1-butanol / acetone", for example, is used in connection with the present invention, it means the combined use of 1-butanol and acetone. Thus, according to the present invention, the solvent used to dissolve a DM hydrochloride powder may
30 comprise not only methanol alone, but also a mixture of methanol and 1-butanol or a mixture of methanol, 1-butanol and acetone,

hexane or diisopropyl ether, provided that the mixture can dissolve the DM hydrochloride powder. Then, as a solvent for crystallization purposes, 1-butanol or a mixture of 1-butanol and acetone, hexane or diisopropyl ether is added to the DM hydrochloride solution thus
5 obtained, so that a crystalline DM hydrochloride is formed. This crystallization step may be carried out by, after the addition of the aforesaid solvent for crystallization purposes, allowing the solution to stand at a temperature of about 5 to 35°C and preferably at room temperature (18 to 27°C), optionally with cooling (to about 5°C) and
10 optionally with gentle stirring. The crystalline DM hydrochloride so precipitated may be collected by a per se known technique such as filtration or centrifugation.

DM hydrochloride may be obtained as a commercial product, or may be prepared according to the process described in
15 Japanese Patent Laid-Open No. 21394/84 (corresponding to U.S. Patent No. 4,592,999). As the starting material for use in the process of the present invention, the DM hydrochloride which has been obtained by any method may be used, provided that it suits the purpose of the present invention. However, it is generally favorable
20 to use DM hydrochloride having a purity of not less than 90% and preferably not less than 95%.

The present invention is more specifically explained with reference to the following examples. However, it is not intended to limit the present invention to any of these examples.

25 Example 1 (comparative example)

2 g of DM hydrochloride was dissolved in 20 mL of methanol. At room temperature, 200 mL of acetone was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C
30 for 16 hours) to obtain 1.2 g of a reddish-brown powder. The result of measurement of this powder according to the X-ray powder diffrac-

tion method is shown as a) in FIG. 1. The measuring conditions included a step angle of 0.02° , a counting time of 1.0 second, a tube voltage of 40.0 kV, and a tube current of 20.0 mA (the same shall apply hereinafter).

5 Example 2 (the present invention)

2 g of DM hydrochloride was dissolved in 20 mL of methanol. At room temperature, 200 mL of 1-butanol was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 1.4 g of a reddish-brown crystalline powder. The result of measurement of this powder according to the X-ray powder diffraction method is shown as b) in FIG. 1.

Example 3 (comparative example)

2 g of DM hydrochloride was dissolved in 20 mL of methanol. At room temperature, 200 mL of ethanol was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 0.9 g of a reddish-brown crystalline powder. The result of measurement of this powder according to the X-ray powder diffraction method is shown as c) in FIG. 1.

Example 4 (comparative example)

2 g of DM hydrochloride was dissolved in 20 mL of methanol. At room temperature, 200 mL of diethyl ether was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 1.5 g of a reddish-brown powder. The result of measurement of this powder according to the X-ray powder diffraction method is shown as d) in FIG. 1.

Example 5 (comparative example)

30 2 g of DM hydrochloride was dissolved in 20 mL of methanol. At room temperature, 200 mL of 1-propanol was added to the

solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 0.9 g of a reddish-brown powder. The result of measurement of this powder according to the X-ray powder diffraction method is shown as e) in FIG. 1.

Example 6 (comparative example)

2 g of DM hydrochloride was dissolved in 20 mL of methanol. At room temperature, 200 mL of 2-propanol was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 1.3 g of a reddish-brown powder. The result of measurement of this powder according to the X-ray powder diffraction method is shown as f) in FIG. 1.

Example 7 (comparative example)

2 g of DM hydrochloride was dissolved in 20 mL of methanol. At room temperature, 200 mL of n-hexane was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 1.3 g of a reddish-brown crystalline powder. The result of measurement of this powder according to the X-ray powder diffraction method is shown as g) in FIG. 1.

Example 8 (comparative example)

2 g of DM hydrochloride was dissolved in 20 mL of methanol. At room temperature, 200 mL of isopropyl ether was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 1.6 g of a reddish-brown crystalline powder. The result of measurement of this powder according to the X-ray powder diffraction method is shown as h) in FIG. 1.

Example 9 (the present invention)

0.5 g of DM hydrochloride was dissolved in 5 mL of metha-

nol. At room temperature, 50 mL of a mixture (2 : 3) of 1-butanol and acetone was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 0.28 g of a reddish-brown crystalline powder. The result of measurement of this powder according to the X-ray powder diffraction method showed the same pattern as that of b) in FIG. 1.

Example 10 (the present invention)

0.5 g of DM hydrochloride was dissolved in 5 mL of methanol. At room temperature, 50 mL of a mixture (3 : 2) of 1-butanol and hexane was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 0.38 g of a reddish-brown crystalline powder. The result of measurement of this powder according to the X-ray powder diffraction method showed the same pattern as that of b) in FIG. 1.

Example 11 (the present invention)

0.5 g of DM hydrochloride was dissolved in 5 mL of methanol. At room temperature, 50 mL of a mixture (3 : 2) of 1-butanol and diisopropyl ether was added to the solution, resulting in the formation of a precipitate. This precipitate was collected by filtration and dried (under reduced pressure at 60°C for 16 hours) to obtain 0.38 g of a reddish-brown crystalline powder. The result of measurement of this powder according to the X-ray powder diffraction method showed the same pattern as that of b) in FIG. 1.

Example 12 (tests for hygroscopicity)

Samples of the powders (or crystalline powders) obtained in Examples 1-8 were stored at 30°C and at relative humidities ranging from 32 to 91%. Their moisture contents were measured until a steady state was reached. The critical relative humidities calculated from the increases or decreases in moisture content are

shown in Table 1 below.

Table 1

5	Powder	Ex.1	Ex.2	Ex.3	Ex.4	Ex.5	Ex.6	Ex.7	Ex.8
10	Critical relative humidity (%)	34	73	41	28	29	29	41	53

It can be seen from the above-described results that the crystalline DM hydrochloride obtained in Example 2 (the present invention) has very low hygroscopicity.

15 Example 13 (tests for chemical stability)

Each of the same samples as used in Example 12 was placed in a hermetically sealed container and stored at 60°C for 1 month. Then, the sample was analyzed by HPLC to determine the DM content in the sample. The results thus obtained are shown in
20 Table 2 below.

Table 2

25	Powder	Ex.1	Ex.2	Ex.3	Ex.4	Ex.5	Ex.6	Ex.7	Ex.8
30	Amount of remaining DM (%)	91.4	100	97.1	90.4	97.5	94.2	97.2	96.5

It can be seen from the above-described results that the crystalline powder of Example 2 has excellent chemical stability. (Conditions for analysis by HPLC)

Column: YMC A-312 (ODS) (manufactured by YMC Co.,
35 Ltd.).

Mobile phase: Acetonitrile-water (38 : 62) (adjusted to pH 2.2 with phosphoric acid).

Flow velocity: About 1.5 ml/min.

Detection: 254 nm.

Example 14 (residual solvent content)

Each of the same samples as used in Example 12 was
5 analyzed by gas chromatography (GC) to determine its residual
solvent content. The results thus obtained are shown in Table 2
below.

Table 3

Crystalline form

15	Powder	Ex.1	Ex.2	Ex.3	Ex.4	Ex.5	Ex.6	Ex.7	Ex.8
	Residual solvent content (%)	0.14	0.40	0.03	0.50	0.19	0.18	0.05	0.95

20 It can be seen from the above-described results that the
residual solvent content of the crystalline powder of Example 2 is
within an acceptable limit.

(Operating conditions for analysis by GC)

Detector: Flame ionization detector.

25 Column: Shimadzu CBP 10-S25-050.

Column temperature: Operated at 40°C for 5 minutes, and
then raised to 80°C in 5 minutes and held at that
temperature.

30 Vaporization chamber temperature: A constant temperature
around 200°.

Carrier gas: Helium.

Flow rate: A constant flow rate at which the retention time of
an internal standard substance (dioxane) is about
6 minutes.

Exploitability in Industry

- The present invention provides crystalline forms of DM hydrochloride showing a reduction in hygroscopicity and residual solvent content and an improvement in chemical stability, as well as
- 5 a process which can produce them easily. Accordingly, the present invention may be utilized, for example, in the field of the manufacture of medicines and bulk materials for medicines.